

Model	AC Input	200-240VAC, 4.5A, 47-53Hz					100-240VAC, 8.5A-4.5A, 47-63Hz					Total Max Output Power
	DC Output	+3.3V	+5V	+12V	-12V	+5VSB	+3.3V	+5V	+12V	-12V	+5VSB	
AD-Z550	Max. Output Current	20A	20A	41A	0.4A	2.5A	20A	20A	41A	0.4A	2.5A	550W
	Max.combined	100W		492W	4.8W	12.5W	100W		492W	4.8W	12.5W	

### CABLE LENGTH

ATX CABLE	1X500mm
EPS CABLE	1x600mm
PCIE CABLE	1x500mm,650mm
SATA CABLE	1x400mm,550mm,700mm
AC POWER	1x 1200mm
SATA/Molex/FDD CABLE	1x400mm,550mm,700mm,850mm,1000mm

### CONNECTOR QUANTITY

(20+4) PIN ATX	1x
EPS(CPU)	1x8Pin(4+4)
PCIE	2x8Pin(6+2)
SATA	5x
Molex	2x
Floppy	1x

Dimension (HxWxD)	86mm x 150mm x 165mm
Color Box Size (HxWxD)	115mm x 185mm x 240mm



Type Approved  
Safety  
Regular Production  
Surveillance  
[www.tuv.com](http://www.tuv.com)  
ID: 1415042621